

ARCHITECTURAL SPECIFICATIONS

PANASONIC ADVANCED VENTILATION SERIES

FAN/LIGHT COMBINATION CEILING MOUNTED VENTILATING FANS

FV-07VQL3 WhisperLite

Ventilating fan and light shall be of the ceiling mount, Energy Star rated type, with no less than 70 CFM and no more than 0.3 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge. Fan power consumption shall be no greater than 18.4 watts and Energy Star rated with efficiency rating of no less than 3.8 cfm/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 4". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Lamps shall be of the compact fluorescent type with the fan utilizing no less than two 13-watt energy efficient, compact fluorescent lamps. Night-light feature shall be included.

FV-08VQL3 WhisperLite

Ventilating fan and light shall be of the ceiling mount, Energy Star rated type, with no less than 90 CFM and no more than 0.6 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge. Fan power consumption shall be no greater than 20 watts and Energy Star rated with efficiency rating of no less than 4.5 cfm/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 4". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Lamps shall be of the compact fluorescent type with the fan utilizing no less than two 13-watt energy efficient, compact fluorescent lamps. Night-light feature shall be included.

FV-11VQL3 WhisperLite

Ventilating fan and light shall be of the ceiling mount, Energy Star rated type, with no less than 110 CFM and no more than 1.2 sone as certified by the Home Ventilating Institute (HVI) at 0.1 static pressure in inches water gauge. Fan power consumption shall be no greater than 25.5 watts and Energy Star rated with efficiency rating of no less than 4.3 cfm/watt. The motor shall be totally enclosed, four pole condenser type engineered to run continuously. Power rating shall be 120v/60Hz. Duct diameter shall be no less than 4". Fan shall be UL and cUL listed for tub/shower enclosure when used with GFCI branch circuit wiring. Lamps shall be of the compact fluorescent type with the fan utilizing no less than two 13-watt energy efficient, compact fluorescent lamps. Night-light feature shall be included.